

# หัวอ่านแสดงค่าน้ำหนัก LP7510A (สแตนเลส) สำหรับเครื่องชั่ง Bench และ Floor

## LP7510 High Precision Weighing indicator

### FEATURES & BENEFITS

NTEP & OIML Approval  
Stainless steel or mild steel Enclosure  
0.8" LED or LCD display with backlight  
Function: ON/OFF, Total, Gross, Net, Tare, Zero, Count, Print, Kg/lb, Hold  
Check weighing, Animal weighing  
With Date and Time  
Full Duplex RS-232 Serial Port  
Drives up to six 350 load cells  
Display up to 30,000d

### Option:

Full Duplex RS485 serial port  
In-built printer  
4-20mA analog output  
IP67 stainless steel Enclosure  
Ex approval

### SPECIFICATIONS

Accuracy Class: III, n=5000e  
Max division 30,000d  
Zero stability error  $TK_0 < 0.1\mu V/K$   
Span stability error  $TK_{spn} < \pm 6 \text{ ppm}/K$   
Conversion time 50 ms  
Sensitivity (internal)  $0.12\mu V/\text{count}$   
Input voltage -30~30mV DC  
Excitation circuit 5 VDC, 4 wire connection, all strain gauge,  
min. 50Ω e.g.: 6 load cell of 350Ω  
AC power AC100~250V  
DC power DC6V/4Ah rechargeable batter,700mA,  
Operation temperature -10 °C to 40 °C  
Storage temperature -40 °C to 70 °C  
Operation humidity =85%RH  
Indicator Dimensions: 200mm(L) X 75mm(W) X 183mm(H)



Dot Printer



Mini Printer



Mini Remote Display

## ตัวอย่างปริ๊นรายงานชั่งน้ำหนัก

Date: 58.02.11  
Time: 12:19:12  
Gross 11.10kg

Date: 58.02.11  
Time: 12:19:32  
Gross 11.20kg

Date: 58.02.11  
Time: 12:20:19  
Net 11.05kg  
Tare 11.20kg  
Gross 22.30kg

Date: 58.02.11  
Time: 12:20:29  
Net 11.05kg  
Tare 11.20kg  
Gross 22.30kg

Date: 58.02.11  
Time: 12:21:05  
n001 11.10kg  
n002 11.10kg  
n003 11.05kg  
n004 11.10kg  
Total: 44.30kg