

เครื่องสำรองกระแสไฟฟ้า POWERPLUS UPS

Technical Specification

MODEL (รุ่น) **POWERPLUS1500-110** **POWERPLUS-2000-110**

Technology **Line Interactive UPS with Stabilizer**

Input (ภาคไฟฟ้าขาเข้า)

Power Rating	1500 VA/ 900 W	2000 VA/ 1200 W
Voltage	100,110Vac +/-25%	
Frequency	50 Hz. +/-10%	

Output (ภาคไฟฟ้าขาออก)

Voltage Stabilizer	100,110Vac +/-5%
Voltage Back-Up	100,110Vac +/- 1% (Depend on load)
Frequency	50 Hz. +/-0.1%
Wave Form	Modify Sine Wave

Battery & System Protection (แบตเตอรี่ และระบบการป้องกัน)

Overload	Auto cut-off (backup mode)
Battery Type	Sealed lead acid maintenance free
Battery Modules	12 V7.8Ah x 4(1500VA) 12 V7.8Ah x 6(2000 VA)
Back-up time	20-30 mins. (User Requirement)
Recharge time	6-8 Hours (90% after fully discharged)
Battery Protection	Low Battery Shutdown
Control Software	RUPS-2000(Optional)
Transfer Time	2 ms (In Phase Transfer)
Over Voltage	Power Line to Back-Up 220Vac +25%
Under Voltage	Power Line to Back-Up 220Vac -25%
Operating Temperature	0-45°C
Operating Humidity	0-95% (Non-Condensing)

Features & Indicator (คุณสมบัติเด่นและการแสดงผล)

Battery Level	Yes
Audible Alarm	Battery Backup, Low Battery, Shutdown.
LEDs Indicator	On-Line, Backup, Low Battery, System Fail

Dimension (มิติของเครื่อง)

Size (WxHxD,mm.)	180 x 360 x 500 mm.	
Weight (Kgs.)	28 Kgs.	34 Kgs.

Above Specification are subject to change without prior notice